



# PRODUCT DATA SHEET

**multivis 20W50**  
SJ/CF4  
Code: 1000

**multivis 20W50** is suitable for the lubrication of older types of cars, light commercials and diesel engines where API SJ petrol rating or CF4 diesel rating is required.

## SPECIFICATIONS

**multivis 20W50** meets or exceeds the following specifications.

- API SJ/CF4
- SAE 20W50
- CCMC G4, D4, PD-2
- US MILITARY MIL-L-465152D

## APPLICATIONS

**multivis 20W50** is suitable for L.P.G. vehicles and is particularly suited for use in four stroke petrol engines equipped with emission control and PVC systems and will provide protection against wear, sludge formation and acid corrosion.

**multivis 20W50** is also suitable for use in diesel engines both naturally aspirated and turbo charged.

**multivis 20W50** will assist in controlling oil consumption in worn engines and also protect against oxidation and will maintain its viscosity characteristics over the service life and provide a high level of protection against wear.

**multivis 20W50** assists in maintaining engine cleanliness.

## TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	20W50
Specific gravity at 15 C	0.892
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	180
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	18.6
Viscosity index	115
TBN, mgKOH/g	7.5
Sulphated ash, %	0.96

**PACKAGE SIZE** 4, 5, 20,200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.