



# PRODUCT DATA SHEET

## ultra motor oil 10W30 SN/CF Code: 1010

**ultra motor oil 10W30** is a premium quality engine oil which has been formulated with the optimal additive technology to meet the required specifications.

### SPECIFICATIONS

**ultra motor oil 10W30** meets or exceeds the following specifications.

- API SN/CF
- SAE 10W30

### APPLICATIONS

**ultra motor oil 10W30** is suitable for modern engines designed to provide improved fuel economy, lower exhaust emissions, high specific horsepower and longer service interval between oil changes.

**ultra motor oil 10W30** is also suitable for use in diesel engines both naturally aspirated and turbo charged. It is recommended for use in multivalve and fine tolerance engine/transmission combinations where an oil of 7.5W30 or 10W30 viscosity range is specified.

**ultra motor oil 10W30** will assist in controlling oil consumption in worn engines and also protect against oxidation and will maintain its viscosity characteristics over the service life and provide a high level of protection against wear.

**ultra motor oil 10W30** assists in maintaining engine cleanliness, contains no friction modifiers and is suitable in wet clutch applications.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W30
Specific gravity at 15 C	0.87
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	83
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	10.8
Viscosity index	116
<b>PACKAGE SIZE</b>	3, 4, 20, 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.