



PRODUCT DATA SHEET

premium motor oil

15W40 SN/CF

Code: 1020

Premium Motor oil 15W40 is a high viscosity index ensuring quick circulation of oil to all moving parts during cold weathers starts, providing additional wear protection during this critical time of an engine's operation.

SPECIFICATIONS

Austec 10W40 meets or exceeds the following specifications.

- API SN/CF
- SAE 15W40
- JASO MA 2

APPLICATIONS

Premium Motor Oil is motor oil for use in late model multivalve engines. Assists in maintaining engine cleanliness, conserving energy and optimising fuel economy. Suitable for petrol, light diesel, turbo charged and L.P.G.

Premium Motor Oil meets or exceeds the requirements of an SN/CF engine oil and provides a high level of protection against wear, sludge formation and acid corrosion.

Premium Motor Oil assists in maintaining engine cleanliness in all engines and additionally assists in energy conservation and fuel economy.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40
Specific gravity at 15 C	0.87
Viscosity at 40 C, mm ² /s (cSt)	112
Viscosity at 100 C, mm ² /s (cSt)	14.5
Viscosity index	132
PACKAGE SIZE	4, 5, 20, 200 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.