



# PRODUCT DATA SHEET

## global diesel 15W40

CK4/SN  
code: 1300

**global diesel 15W40 CK4/SN** is a premium diesel engine oil to meet the latest specifications for engines with DPF (diesel particulate filter) and EGR (exhaust gas recycling) using low sulphur fuels.

### SPECIFICATIONS

**global diesel 15W40 CK4/SN** meets the following specifications.

- API CK4/SN
- SAE 15W40
- MB 228.3
- ACEA E9
- Caterpillar ECF
- Cummins

### APPLICATIONS

**global diesel 15W40** is formulated with premium quality base oil together with an optimum low ash additive package which is recommended for the latest model engines including those fitted with turbo chargers.

**global diesel 15W40** provides high level of protection against wear, sludge formation and acid corrosion.

**global diesel 15W40** assists in maintaining engine cleanliness in all engines and helps in energy conservation and fuel economy.

**global diesel 15W40** is a low phosphorus oil suitable for all four stroke diesel and petrol engines making it ideal for mixed fleets and is also backward compatible with all API diesel ratings prior to CJ4.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40
Specific gravity at 15 C	0.88
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	110
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14
Viscosity index	130
TBN mgKOH/g	8

**PACKAGE SIZE** 20, 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.