



# PRODUCT DATA SHEET

## ultra diesel 15W40

CI4/SL  
code: 1310

**ultra diesel 15W40 CI4/SL** is a diesel engine oil which provides excellent performance for four stroke turbo charged and normally aspirated diesel engines.

### SPECIFICATIONS

**ultra diesel 15W40 CI4/SL** meets the following specifications.

- API CI4/SL
- SAE 15W40
- MB 228.3
- ACEA E7
- Caterpillar ECF
- Cummins

### APPLICATIONS

**ultra diesel 15W40** is formulated with high quality base oil together with an optimum mid SAPs (sulphated ash, phosphorus and sulphur) additive package which is recommended for the latest model engines including those fitted with turbo chargers.

**ultra diesel 15W40** provides high level of protection against wear, sludge formation and acid corrosion.

**ultra diesel 15W40** assists in maintaining engine cleanliness in all engines and helps in energy conservation and fuel economy.

**ultra diesel 15W40** is a mid SAPs oil suitable for all four stroke diesel and petrol engines making it ideal for mixed fleets and is also backward compatible with all API diesel ratings prior to CI4.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40
Specific gravity at 15 C	0.88
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	110
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14
Viscosity index	130

**PACKAGE SIZE** 7, 20, 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.