



# PRODUCT DATA SHEET

## multi diesel 15W40 CH4/SL Code: 1410

**multi diesel 15W40 SL/CH4** is a versatile multifunctional oil which offers improved wear protection for pistons in current generation multi-valve and conventional engines. It has good soot control, reduced sludge deposits and less oil thickening.

### SPECIFICATIONS

**multi diesel 15W40 CH4/SL** meets or exceeds the following specifications.

- API CH4/ SL
- SAE 15W40
- JASO MA2
- API CG4/SL

### APPLICATIONS

**multi diesel 15W40** has a high viscosity index ensuring quick circulation of oil to all moving parts during cold weather starts, providing additional wear protection during this critical time of an engine's operation.

**multi diesel 15W40** is suitable for all late model engine including those fitted with turbo chargers. Ideal for use in L.P.G. fuelled vehicles and diesel engines where API CH4 performance is required.

**multi diesel 15W40** meets or exceeds the requirements of an SL/CH4 engine oil and provides high level of protection against wear, sludge formation and acid corrosion. It is also backward compatible with all API diesel ratings prior to CH4.

**multi diesel 15W40** assists in maintaining engine cleanliness in all engines and additionally helps in energy conservation and fuel economy.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40
Specific gravity at 15 C	0.88
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	112
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14.5
Viscosity index	132
TBN mgKOH/g	9.1
Sulphated Ash %	0.95

**PACKAGE SIZE** 7, 20, 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.