



PRODUCT DATA SHEET

ATF DXR III

Code: 4010

ATF DXR III is a premium quality mineral multi-vehicle automatic transmission fluid that meets the requirements of GM Dexron III H specifications.

SPECIFICATIONS

ATF DXR III meets or exceeds the following specifications.

- GENERAL MOTORS- DEXRON III H, II
- FORD MERCON
- TOYOTA T-III,IV
- ALLISON C4
- MAN 339 Type Z-1
- HONDA Z1
- SPERRY VICKERS HYDRAULIC PUMP SYSTEMS
- SUNSTRAND HYDRAULIC PUMP SYSTEMS
- JASO 1A
- DENISON HYDRAULIC PUMP SYSTEMS
- ZF: TE-ML-14A

APPLICATIONS

ATF DXR III is a high viscosity index fluid containing superior additive technology which provides exceptional thermal stability as well as oxidation resistance and sludge control.

ATF DXR III should be used wherever Dexron 111 is specified and is suitable for all General Motors four speed automatic transmissions.

ATF DXR III may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

ATF DXR III is also approved for use where Allison C4 fluid is recommended.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Specific gravity at 15 C	0.866
Viscosity at 40 C, mm ² /s (cSt)	34
Viscosity at 100 C, mm ² /s (cSt)	7.1
Viscosity Index	170
Flash Point C	200
Colour	Red

PACKAGE SIZE 4, 5, 20, 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.